Model Number					
137B28					

## **ICP® PRESSURE SENSOR**

[1]

[2]

[3]

[1] [2]

Revision: NR ECN #: 47071

Performance	<u>ENGLISH</u>	SI
Measurement Range(for ±1V output)	1 kpsi	6895 kPa
Sensitivity(± 15 %)	1 mV/psi	.145 mV/kPa
Maximum Pressure	5 kpsi	34,474 kPa
Resolution	8.5 mpsi	.059 kPa
Resonant Frequency	≥ 400 kHz	≥ 400 kHz
Rise Time(Incident)	≤ 6.5 µ sec	≤ 6.5 µ sec
Non-Linearity	≤ 1.0 % FS	≤ 1.0 % FS
Environmental		
Temperature Range(Operating)	-100 to +275 °F	-73 to +135 °C
Temperature Coefficient of Sensitivity	≤ 0.05 %/°F	≤ 0.090 %/°C
Electrical		
Discharge Time Constant(at room temp)	≥ 0.2 sec	≥ 0.2 sec
Excitation Voltage	20 to 30 VDC	20 to 30 VDC
Constant Current Excitation	2 to 20 mA	2 to 20 mA
Output Impedance	≤ 100 Ohm	≤ 100 Ohm
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC
Physical		
Sensing Geometry	Compression	Compression
Sensing Element	Quartz	Quartz
Housing Material	Aluminum	Aluminum
Diaphragm	Invar	Invar
Sealing	Epoxy	Epoxy
Electrical Connector	4-Pin	4-Pin
Weight	16.1 oz	456 gm



All specifications are at room temperature unless otherwise specified.

In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB Group, Inc.

## **OPTIONAL VERSIONS**

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

## NOTES:

- [1] Two identically spec'd elements spaced 10cm apart see drawing #65310 for details. Individual calibration certs supplied for each channel.

- [3] Zero-based, least-squares, straight line method.
   [4] See PCB Declaration of Conformance PS023 for details.

## SUPPLIED ACCESSORIES:

Model PCS-6 Calibration of Series 134, 137, and 138 (2)

Entered: LK	Engineer: DK	Sales: RWM	Approved: BAM	Spec Number:
Date: 7/26/2017	Date: 7/26/2017	Date: 7/26/2017	Date: 7/26/2017	67325



Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com