

Performance

	ENGLISH	SI	
Sensitivity (± 15 %)	10 mV/lb	2248 mV/kN	
Measurement Range (Compression)	500 lb	2.224 kN	
Measurement Range (Tension)	500 lb	2.224 kN	
Maximum Static Force (Compression)	3000 lb	13.5 kN	
Maximum Static Force (Tension)	500 lb	2.224 kN	
Broadband Resolution (1 to 10,000 Hz)	0.005 lb-rms	0.02 N-rms	[1]
Low Frequency Response (-5 %)	0.0003 Hz	0.0003 Hz	[2]
Upper Frequency Limit	36 kHz	36 kHz	[3]
Non-Linearity	≤ 1 % FS	≤ 1 % FS	[4]

Environmental

Temperature Range	-65 to +250 °F	-54 to +121 °C	
Temperature Coefficient of Sensitivity	≤ 0.05 %/°F	≤ 0.09 %/°C	

Electrical

Discharge Time Constant (at room temp)	≥ 2000 sec	≥ 2000 sec	
Excitation Voltage	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	≤ 100 ohm	≤ 100 ohm	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
Spectral Noise (1 Hz)	0.000211 lb/√Hz	0.000942 N/√Hz	[1]
Spectral Noise (10 Hz)	0.000109 lb/√Hz	0.000488 N/√Hz	[1]
Spectral Noise (100 Hz)	0.0000387 lb/√Hz	0.000173 N/√Hz	[1]
Spectral Noise (1 kHz)	0.0000086 lb/√Hz	0.0000385 N/√Hz	[1]
Output Polarity (Compression)	Positive	Positive	

Physical

Stiffness	6 lb/μin	1.05 kN/μm	[1]
Size (Hex x Height x Sensing Surface)	0.625 in x 0.625 in x 0.500 in	15.88 mm x 15.88 mm x 12.7 mm	
Weight	0.80 oz	22.7 gm	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Hermetic	Hermetic	
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack	
Electrical Connection Position	Side	Side	
Mounting Thread	10-32 Female	10-32 Female	
Mounting Torque (Recommended)	16 to 20 in-lb	181 to 226 N-cm	

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

N - Negative Output Polarity		
Output Polarity (Compression)	Negative	Negative
W - Water Resistant Cable		
Electrical Connector	Sealed Cable	Sealed Cable
Electrical Connection Position	Side	Side

NOTES:

- [1] Typical.
 [2] Calculated from discharge time constant.
 [3] Estimated using rigid body dynamics calculations.
 [4] Zero-based, least-squares, straight line method.
 [5] See PCB Declaration of Conformance PS023 for details.

SUPPLIED ACCESSORIES:

Model 080A81 Thread Locker (1)
 Model 081B05 Mounting Stud (10-32 to 10-32) (2)
 Model 084A03 Impact Cap (1)
 Model M081A62 Mounting stud, 10-32 to M6 x 1, BeCu with shoulder (2)

Entered: BLS	Engineer: MFL	Sales: MFL	Approved: DMB	Spec Number:
Date: 5-1-06	Date: 5-2-06	Date: 5/3/06	Date: 5/2/06	8396



[5]

All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB Group, Inc.

PCB PIEZOTRONICS
 FORCE / TORQUE DIVISION
 3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001
 Fax: 716-684-8877
 E-Mail: force@pcb.com