

Performance	ENGLISH	SI	
Sensitivity (± 15 %)	5 mV/lb	1124 mV/kN	
Measurement Range (Compression)	1000 lb	4.448 kN	
Measurement Range (Tension)	500 lb	2.224 kN	
Maximum Static Force (Compression)	6000 lb	26.69 kN	
Maximum Static Force (Tension)	500 lb	2.224 kN	
Broadband Resolution (1 to 10,000 Hz)	0.01 lb-rms	0.04448 N-rms	[1]
Low Frequency Response (-5 %)	0.0003 Hz	0.0003 Hz	[2]
Upper Frequency Limit	36 kHz	36 kHz	[3]
Non-Linearity	≤ 1 % FS	≤ 1 % FS	[4]
<b>Environmental</b>			
Temperature Range	-65 to +250 °F	-54 to +121 °C	
Temperature Coefficient of Sensitivity	≤ 0.05 %/°F	≤ 0.09 %/°C	
<b>Electrical</b>			
Discharge Time Constant (at room temp)	≥ 2000 sec	≥ 2000 sec	
Excitation Voltage	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	≤ 100 ohms	≤ 100 ohms	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
Spectral Noise (1 Hz)	0.000798 lb/√Hz	0.00356 N/√Hz	[1]
Spectral Noise (10 Hz)	0.000286 lb/√Hz	0.00128 N/√Hz	[1]
Spectral Noise (100 Hz)	0.0000860 lb/√Hz	0.000384 N/√Hz	[1]
Spectral Noise (1 kHz)	0.0000276 lb/√Hz	0.000123 N/√Hz	[1]
Output Polarity (Compression)	Positive	Positive	
<b>Physical</b>			
Stiffness	6 lb/μin	1.05 kN/μm	[1]
Size (Hex x Height x Sensing Surface)	0.625 in x 0.625 in x 0.500 in	15.88 mm x 15.88 mm x 12.7 mm	
Weight	0.80 oz	22.7 gm	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Hermetic	Hermetic	
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack	
Electrical Connection Position	Side	Side	
Mounting Thread	10-32 Female	Not Applicable	
Mounting Torque (Recommended)	16 to 20 in-lb	181 to 226 N-cm	

OPTIONAL VERSIONS		
Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.		
<b>N</b> - Negative Output Polarity	Negative	Negative
Output Polarity (Compression)		
<b>W</b> - Water Resistant Cable	Sealed Cable	Sealed Cable
Electrical Connector	Side	Side
Electrical Connection Position		

**NOTES:**  
 [1] Typical.  
 [2] Calculated from discharge time constant.  
 [3] Estimated using rigid body dynamics calculations.  
 [4] Zero-based, least-squares, straight line method.  
 [5] See PCB Declaration of Conformance PS023 for details.

**SUPPLIED ACCESSORIES:**  
 Model 080A81 Thread Locker (1)  
 Model 081B05 Mounting Stud (10-32 to 10-32) (2)  
 Model 084A03 Impact Cap (1)  
 Model M081A62 Mounting stud, 10-32 to M6 x 1, BeCu with shoulder (2)

<b>ICP® Force</b>				
Entered: <i>ASR</i>	Engineer: <i>ASR</i>	Sales: <i>gjm</i>	Approved: <i>DMB</i>	Spec Number:
Date: <i>7/9/03</i>	Date: <i>7/9/03</i>	Date: <i>7/9/03</i>	Date: <i>7/9/03</i>	<b>8982</b>



All specifications are at room temperature unless otherwise specified.  
 In the interest of constant product improvement, we reserve the right to change specifications without notice.  
 ICP® is a registered trademark of PCB Group, Inc.

**PCB PIEZOTRONICS™**  
**FORCE / TORQUE DIVISION**  
 3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001  
 Fax: 716-684-8877  
 E-Mail: force@pcb.com