

Model Number
3501A1260KG

HIGH AMPLITUDE MEMS SHOCK ACCELEROMETER

Revision: NR
ECN #:

	ENGLISH	SI	
Performance			
Sensitivity(± 50 %)(at 10 VDC excitation)	0.003 mV/g 0.0003 mV/V/g	0.0003 mV/(m/s ²) 0.00003 mV/V/(m/s ²)	[1] [7]
Measurement Range	± 60 kg	± 588,400 m/s ² pk	
Frequency Range(± 1 dB)	0 to 20,000 Hz	0 to 20,000 Hz	
Resonant Frequency	>120 kHz	>120 kHz	
Damping Ratio	2 % Critical	2 % Critical	[5]
Non-Linearity	± 1 %	± 1 %	
Transverse Sensitivity	≤ 3 %	≤ 3 %	

	ENGLISH	SI	
Environmental			
Overload Limit(Shock)	± 100,000 g pk	± 980,665 m/s ² pk	[4]
(Mechanical Stops)	≥ 80 kg	≥ 782,534 m/s ² pk	
Temperature Range(Storage)	-65 to 250 °F	-54 to 121 °C	
(Operating)	-65 to 250 °F	-54 to 121 °C	
Temperature Coefficient of Sensitivity	-0.11 %/°F	-0.20 %/°C	[5]
Zero g Offset Temperature Shift	± 10 mV	± 10 mV	[6]
Base Strain Sensitivity	0.3 g/με	2.94 (m/s ²)/με	[5]

	ENGLISH	SI	
Electrical			
Excitation Voltage(Maximum)	15.0 VDC	15.0 VDC	
Current Consumption	<3 mA	<3 mA	
Input Resistance(± 2000 ohm)	6000 ohm	6000 ohm	[1]
Output Resistance(± 2000 ohm)	6000 ohm	6000 ohm	[1]
Offset Voltage	-40 to +40 mVDC	-40 to +40 mVDC	[1]
Settling Time	0.01 sec	0.01 sec	[2]
Electrical Isolation(Case)	≥ 10 ⁸ ohm	≥ 10 ⁸ ohm	[3]

	ENGLISH	SI	
Physical			
Sensing Element	Piezoresistive MEMS	Piezoresistive MEMS	
Sensing Geometry	Full Active	Full Active	
Housing Material	Titanium	Titanium	
Sealing	Epoxy	Epoxy	
Size (Hex x Height)	3/8 in x .50 in	3/8 in x 12.7 mm	
Weight(without cable)	0.088 oz	2.5 gm	[5]
Electrical Connector	Integral Cable	Integral Cable	
Electrical Connection Position	Side	Side	
Cable Type	034 4-cond Shielded	034 4-cond Shielded	
Cable Termination	Pigtail Ends	Pigtail Ends	
Cable Length	10 ft	3.05 m	
Mounting	Integral Stud	Integral Stud	
Mounting Thread	1/4-28 Male	1/4-28 Male	

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

M - Metric Mount		
Mounting Thread	M6 x 0.75 Male	M6 x 0.75 Male

NOTES:

- [1] Verified with test data provided on supplied calibration certificate.
- [2] Settling Time is the maximum time after power-up for the Offset Voltage to be within +/-2% of Measurement Range output of the final offset value. Mounting surface must be at thermal equilibrium.
- [3] Individually tested to ensure compliance with specified value.
- [4] Half-sine pulse duration, ≥ 20 μsec.
- [5] Typical.
- [6] -65 to +250 °F, ref. 75 °F (-54 to +121 °C, ref. 24 °C)
- [7] Sensitivity is proportional to excitation voltage, and at other excitation values, sensitivity can be predicted from the 10VDC calibrated value with a small (<~.5%) increase in uncertainty.

SUPPLIED ACCESSORIES:

Model ACS-62 Shock Calibration of Piezoresistive High Amplitude Accelerometers

Entered: <i>Pat</i>	Engineer: <i>TCG</i>	Sales: <i>RWM</i>	Approved: <i>DJL</i>	Spec Number:
Date: <i>1-19-11</i>	Date: <i>1-17-11</i>	Date: <i>1-8-11</i>	Date: <i>1-8-11</i>	45651



3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001
Fax: 716-685-3886
E-Mail: vibration@pcb.com