

	<u>ENGLISH</u>	<u>SI</u>	
Performance			
Nominal Microphone Diameter	1/2"	1/2"	
Frequency Response Characteristic(at 0° incidence)	Free-Field	Free-Field	
Open Circuit Sensitivity	5.8 mV/Pa	5.8 mV/Pa	[3]
Open Circuit Sensitivity(+/-1.5 dB)	-44.7 dB re 1 V/Pa	-44.7 dB re 1 V/Pa	[3]
Frequency Range(+/-1 dB)	0.25 to 10,000 Hz	0.25 to 10,000 Hz	
Frequency Range(+/-2 dB)	0.13 to 20,000 Hz	0.13 to 20,000 Hz	
Lower Limiting Frequency(-3 dB)	<0.1 Hz	<0.1 Hz	
Inherent Noise(Linear)	23 dB re 20 µPa	23 dB re 20 µPa	[2]
Inherent Noise	20 dB(A) re 20 µPa	20 dB(A) re 20 µPa	[2]
Dynamic Range(3% Distortion Limit)	>134 dB re 20 µPa	>134 dB re 20 µPa	
TEDS Compliant	Yes	Yes	[4]
Environmental			
Temperature Range(Operating)	-40 to +176 °F	-40 to +80 °C	
Temperature Coefficient of Sensitivity(+14 to +158°F (-10 to +70°C))	0.005 dB/°F	0.009 dB/°C	[2][3]
Static Pressure Coefficient	-0.01 dB/kPa	-0.01 dB/kPa	[2][3]
Humidity Coefficient of Sensitivity(0 to 100%, non-condensing)	± 0.001 dB/%RH	± 0.001 dB/%RH	[3]
Influence of Axial Vibration(0.1g (1 m/s ²))	63 dB re 20 µPa	63 dB re 20 µPa	[2]
Electrical			
Polarization Voltage	0 V	0 V	[1]
Excitation Voltage	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Bias Voltage	10 to 14 VDC	10 to 14 VDC	
Maximum Output Voltage	+/-7 Vpk	+/-7 Vpk	
Output Impedance	<50 Ohm	<50 Ohm	
Physical			
Housing Material	Stainless Alloy	Stainless Alloy	
Venting	Rear	Rear	
Electrical Connector	BNC Jack	BNC Jack	
Mounting Thread(Grid)	0.5 - 60 UNS	0.5 - 60 UNS	
Size (Diameter x Height)(with grid)	0.52 in x 4.29 in	13.2 mm x 109.0 mm	
Size (Diameter x Height)(without grid)	0.50 in x 4.25 in	12.7 mm x 108.0 mm	
Weight	1.63 oz	45.8 gm	[2]

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

TLD - TEDS Capable of Digital Memory and Communication Compliant with IEEE 1451.4
Optional Accessory : Model ACS-63 Calibration (with TEDS) of Precision Condenser Microphones and Preamplifiers together (mated pair). (1) replaces Model ACS-42

NOTES:

[1]Prepolarized
[2]Typical.
[3]re 250 Hz
[4]TEDS Capable Digital Memory and Communication, compliant with IEEE P1451.4
[5]See PCB Declaration of Conformance PS064 for details.

SUPPLIED ACCESSORIES:

Model 079A43 Low-Frequency Adaptor (1)
Model ACS-42 Calibration of microphone with preamplifier (1)

Entered: AP	Engineer: MJN	Sales: MV	Approved: MT	Spec Number:
Date: 4/24/2015	Date: 4/24/2015	Date: 4/24/2015	Date: 4/24/2015	59960



All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.
ICP® is a registered trademark of PCB Group, Inc.



Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: info@pcb.com